

What is claimed is:

1. A method of aligning an antenna having a feed/LNBF assembly with a satellite, said method comprising:

electronically coupling a set top box to a television having a television speaker;

electronically coupling the feed/LNBF assembly of the antenna to the set top box;

operating the set top box and television such that a series of tones are emitted from the television speaker which is indicative of the alignment of the antenna with the satellite;

supporting a speaker adjacent to the antenna; and

supporting a transmitter adjacent the television speaker, the transmitter transmitting the series of tones emitted by the television speaker to the speaker.

2. The method of claim 1 wherein the feed/LNBF assembly is supported by a support arm and wherein said supporting a speaker comprises supporting the speaker on the support arm.

3. The method of claim 2 wherein said supporting the speaker on the support arm comprises suspending the speaker from the support arm.

4. The method of claim 2 wherein said supporting the speaker on the support arm comprises clamping the speaker to the support arm.

5. The method of claim 1 wherein said supporting the speaker comprises placing

the speaker on the ground adjacent the antenna.

6. The method of claim 1 wherein the antenna has mounting bracket attached thereto and wherein said supporting the speaker comprises affixing the speaker to the mounting bracket.

7. The method of claim 6 wherein said affixing the speaker to the mounting bracket comprises magnetically attaching the speaker to the mounting bracket.

8. The method of claim 6 wherein said affixing the speaker to the mounting bracket comprises attaching the speaker to the mounting bracket with hook and loop fasteners.

9. The method of claim 6 wherein said affixing the speaker to the mounting bracket comprises suspending the speaker from the mounting bracket.

10. The method of claim 1 wherein said supporting a speaker comprises supporting the speaker on a person located adjacent the antenna.

11. The method of claim 10 wherein said supporting the speaker on a person comprises attaching the speaker to a belt worn by the person.

12. The method of claim 10 wherein said supporting the speaker on the person

comprises supporting the speaker in a holster carried by the person.

13. The method of claim 10 wherein said supporting the speaker on a person comprises affixing the speaker to clothing worn by the person.

14. The method of claim 1 further comprising providing the transmitter in a florescent color.

15. The method of claim 1 wherein the antenna is supported relative to the ground and wherein said supporting the speaker adjacent the antenna comprises placing the speaker on the ground adjacent the antenna.